



Waterline Security Light

LED Replacement/LED Fixture

For: SYM 303.X

FEATURES AND BENEFITS

- Mounts to existing 2" round post or tongue mount
- Rugged construction to handle demanding environments
- Longer lasting and better quality of light
- Multiple beam angles available to suit your environment: 25°, 57°
- Cable: 10' SOOW with SYM1218.3 plug
- Rated for marine use
- ABS Type Approved

PRODUCT SPECIFICATIONS

Lumen Output	11,000 lm
Wattage	<115W
Efficacy	>100 lm/W
Input Voltage	100-277VAC
Housing	Corrosion resistant aluminum
Lens	Impact Resistant— Clear (UL94-5VA rated)
Weight	15 lbs
Mount	2" diameter round post
Dimmable	Non-Dimmable
Color Temperature	4100K
Driver	Field replaceable electronic driver
Operating Temperature	-30°C to 50°C
Power Factor	>.9
Lamp Life	50,000 hours to 70% lumen maintenance
Manufactured	BAA Compliant

ORDERING GUIDE

ENERGY FOCUS
EFO

PRODUCT LINE
FL Flood Light

BEAM SPREAD
303.3 25°
303.4 57°

VERSION
02
LCS Tongue Mount

NSN
Red - 6210-01-682-9459
Blue - 6210-01-682-7777
Amber - 6210-01-682-7776
White - 6230-01-665-6332