



Highbay LED Fixture

LED T8 FIXTURE

The Energy Focus T8 High Bay LED Fixture features a linear, durable steel housing designed to be used with Energy Focus LED lamps for high lumen output applications, such as gymnasiums, auditoriums, conference centers, warehouses.

FEATURES AND BENEFITS

- Durable steel housing
- Available with wire guard accessory
- Designed for Energy Focus TLED lamps
- Linear highbay housing ideal for installations requiring high lumen output. Such as manufacturing facilities, warehouses, rec centers, gymnasiums and more

PRODUCT SPECIFICATIONS

Length	48.25" Fixture
Body	0.6mm steel
Connection	T8 LED ready. Pre-wired, non-shunted lampholders included. Single-end power.
Finish	Highly reflective powder coat finish
Input Voltage	100-277VAC, 50/60hz
Mounting	Suspension or surface mounting
Dimming	Non-dimmable
Lifetime	5-year warranty
Environmental Requirements	Operating temp: -20° to 50°C Storage temp: -30° to 60°C Working humidity: 30% to 85% Storage humidity: 10% to 90% Non-corrosive environments



Non-shunted lampholders included



PRODUCT SPECIFICATION

PARTNUMBER	SIZE	FIXTURE L INCHES	FIXTURE W INCHES	FIXTURE H INCHES	COUNT
LEDF-T8HB-4-4	(48") 4'	48.25	12.3	3.5	4 lamps
LEDF-T8HB-4-6	(48") 4'	48.25	17.3	3.5	6 lamps
LEDF-T8HB-4-8	(48") 4'	48.25	22.6	3.5	8 lamps

RECOMMENDED ENERGY FOCUS LAMPS

PARTNUMBER	SIZE	UNITS	NOMINAL POWER	LUMINOUSFLUX <small>*measured in-fixture</small>	EFFICACY <small>*measured in-fixture</small>
LEDFLT8-840-418-388C	(48") 4'	4	72W	8555lm	115
LEDFLT8-840-418-388C	(48") 4'	6	108W	12833lm	115
LEDFLT8-840-418-388C	(48") 4'	8	144W	17110lm	115

*LED tubes not included, must order separately

ACCESSORIES

- Wire guard for 4 lamp fixture: WG-T8HB-4-4
- Wire guard for 6 lamp fixture: WG-T8HB-4-6
- Wire guard for 8 lamp fixture: WG-T8HB-4-8

WIRING DIAGRAM

