



EnFocus™ gives you dimming and color tuning control of LED lighting with unique advantages including:

- **Simple retrofit installation**
- **Network security**
- **Preservation of high power factor and low THD**
- **Significantly lower installation cost**
- **Sustainable and affordable lighting control**

### FEATURES AND BENEFITS

- EnFocus™ boasts 10-stage dimming and color tuning capabilities
- Patent-pending phase-cut communication technologies over A/C power lines to facilitate dimming and color tuning while maintaining high power factor and low THD
- Provides the most affordable and accessible dimmable and color tuning capabilities available



### PRODUCT SPECIFICATIONS

Length	2' and 4' versions. Meets ANSI Standard
Body	Oval extruded aluminum/ polycarbonate lens
Lens	Frosted
Connection	Medium bi-pin (G13) end cap
Input Voltage	120/277vac, 50/60hz
Driver	Single end power; integrated LED driver
Available colors	2700K - 6500K Color Tuning Model 3500K 4000K 5000K
CRI	>80
Dimming	Proprietary Protocol
Lifetime	L70 ≥ 60,000 hours
Warranty	Lamps: 5-year warranty
Environmental Requirements	<b>Operating temp:</b> -20° to 30°C <b>Storage temp:</b> -30° to 60°C <b>Working humidity:</b> 30% to 85% <b>Storage humidity:</b> 10% to 90% <b>Non-corrosive environments</b>
Power Factor	>0.9
Beam Angle	120°

## DIMMING & COLOR TUNING SPECIFICATION

LAMP PART NUMBER	SIZE	NOMINAL POWER	LUMINOUS FLUX
LEDFLT8-82765-207-5EDCTF	(24") 2'	7W	1050lm
LEDFLT8-82765-411-5EDCTF	(48") 4'	11W	1650lm
LEDFLT8-82765-415-5EDCTF	(48") 4'	15W	2250lm

## DIMMING ONLY MODEL SPECIFICATION

LAMP PART #	SIZE	NOMINAL POWER	LUMINOUS FLUX
LEDFLT8-8XX-207-5EDMF	(24") 2'	7W	1050lm
LEDFLT8-8XX-411-5EDMF	(48") 4'	11W	1650lm
LEDFLT8-8XX-415-5EDMF	(48") 4'	15W	2250lm

XX refers to the option for 3500K, 4000K or 5000K color temperature. (Replace XX with 35, 40 or 50 when selecting).

## ACCESSORIES

- Single lampholder, no wires (Model no. LEDFLSLH-G13NS-SBOG)
- Pair of two (2) lampholders, one with 3' wires (Model no. LEDFLSLH-G13NS-SNETGW)
- Single lampholder, with 3' wires (Model no. LEDFLSLH-G13NS-SBOGW)
- Must use non-shunted lamp holders

